

NETWORK GAT INTERFACE SPECIFICATION V1.0



Gaming Standards Association
S2S Technical Committee

Released: 2016/03/14

GAMINGSTANDARDS.COM

Copyright Page

Document Title: Network GAT Interface Specification v1.0

Release Date: 2016/03/14, by Gaming Standards Association (GSA).

Patents and Intellectual Property

NOTE: The user's attention is called to the possibility that compliance with this [standard/specification] may require use of an invention covered by patent rights. By publication of this [standard/specification], GSA takes no position with respect to the validity of any such patent rights or their impact on this [standard/specification]. Similarly, GSA takes no position with respect to the terms or conditions under which such rights may be made available from the holder of any such rights. Contact GSA for further information.

Trademarks and Copyright

Copyright © 2016 Gaming Standards Association (GSA). All trademarks used within this document are the property of their respective owners. Gaming Standards Association and the puzzle-piece GSA logo are registered trademarks and/or trademarks of the Gaming Standards Association.

This document may be copied in part or in full by members of GSA, or non-members that have been authorized by the GSA Board of Directors, provided that ALL copies must maintain the copyright, trademark and any other proprietary notices contained on/in the materials. NO material may be modified, edited or taken out of context such that its use creates a false or misleading statement or impression as to the positions, statements or actions of GSA.

GSA Contact Information

E-mail: sec@gamingstandards.com

WWW: <http://www.gamingstandards.com>

Table of Contents

I About This Document	iii
I.I Acknowledgements	iii
I.II Document Conventions.....	iii
I.II.I Indicating Requirements, Recommendations, and Options	iii
I.II.II Other Formatting Conventions	iii
I.III Categorization of Standards	iii
Chapter 1	
Network GAT Interface Overview	1
1.1 Introduction.....	2
1.1.1 Terminology	2
1.1.2 HTTP Verb Conventions	3
Chapter 2	
GAT Server Supported HTTP Verbs	5
2.1 Introduction.....	6
2.2 Component Resources.....	7
2.2.1 Component Details	7
2.2.1.1 Resource Information	7
2.2.1.2 Request Parameters:	7
2.2.1.3 Response:	7
2.2.1.4 Request Errors.....	8
2.2.2 Component Search	8
2.2.2.1 Resource Information	8
2.2.2.2 Request Parameters	9
2.2.2.3 Response	9
2.2.2.4 Request Errors.....	9
2.3 Verification Task Resources.....	10
2.3.1 Create Verification Task	10
2.3.1.1 Resource Information	10
2.3.1.2 Request Parameters	10
2.3.1.3 Response	11
2.3.1.4 Request Errors.....	11
2.3.2 Verification Task Details	11
2.3.2.1 Resource Information	11
2.3.2.2 Request Parameters:	12
2.3.2.3 Response Information:	12
2.3.2.4 Request Errors.....	12
2.3.3 Verification Task Search	13
2.3.3.1 Resource Information	13
2.3.3.2 Request Parameters	13
2.3.3.3 Response	13
2.3.3.4 Request Errors.....	13
Chapter 3	
GAT Trusted Source Supported HTTP Verbs	15
3.1 Introduction.....	16
3.2 Expected Results Resources	17
3.2.1 Expected Results Details	17
3.2.1.1 Resource Information	17
3.2.1.2 Request Parameters	17
3.2.1.3 Response	17
3.2.1.4 Request Errors.....	18
Chapter 4	
Data Types	19

4.1 Data Types	20
4.1.1 componentType Enumerations	20
4.1.2 algorithmType Enumerations	20
Chapter 5	
Sample Messages	21
5.1 Component Details	22
5.2 Component Search	23
5.3 Create Verification Task	24
5.4 Verification Task Details	25
5.5 Verification Task Search	26
5.6 Expected Results Detail	27

I About This Document

This document defines requirements that must be met by gaming devices, hosts, and messaging protocols to be compliant with the Network GAT Interface Specification.

I.I Acknowledgements

The Gaming Standards Association would like to express its appreciation to all members of the S2S committee, past and present, for their significant contribution and dedication to the creation of this specification.

I.II Document Conventions

I.II.I Indicating Requirements, Recommendations, and Options

Terms and phrases in this document that indicate requirements, recommendations, and options in the Network GAT Interface Specification are used as defined in the IETF [RFC 2119](#).

In summary:

Requirements:

To indicate requirements, this document uses "MUST", "MUST NOT", "REQUIRED", "SHALL", or "SHALL NOT".

Recommendations:

To indicate recommendations, this document uses "SHOULD", "SHOULD NOT", "RECOMMENDED".

Options:

To indicate **options**, this document uses "MAY" or "OPTIONAL".

I.II.II Other Formatting Conventions

- [Blue](#) text indicates an internal link or external hyperlink to a URL.
- **Bold** (other than in headings) or underlined text is used for emphasis, unless specifically indicated otherwise.
- `Courier New` font is used to indicate JSON components and their values, and other types of code or pseudo code.

I.III Categorization of Standards

To help provide guidance to implementers regarding the maturity and stability of its standards, GSA categorizes its standards as Candidate Standards, Proposed Standards, or Recommended Standards. This specification is categorized as a Candidate Standard.

- Standards identified as Candidate Standards are the least mature; changes to these standards should be expected in future releases.
- Standards identified as Proposed Standards have been reduced to practice and deployed; very few changes to these standards should be expected.

- Standards identified as Recommended are the most mature and have been widely deployed; no changes to these standards should be expected.

Further details about the categorization of standards and extensions can be found in the GSA Policy Handbook.

Chapter 1

Network GAT Interface

Overview

1.1 Introduction

This document describes the Network GAT Interface, which contains commands specifically designed to provide software authentication information required by gaming regulators.

The Network GAT Interface allows a GAT Client to communicate with a GAT Server and request that the GAT Server perform a verification algorithm (such as a hashing algorithm) on components exposed by the GAT Server. These components may include files, executables, loadable modules (such as DLLs), or downloadable content (such as game packages, SWFs, etc.)

The interface gives systems a standard method for reporting the resulting verification data to regulators and other systems. The verification data can be compared to expected results that have been gathered from a GAT Trusted Source or that are stored in a local database on the GAT Client.

1.1.1 Terminology


Within this document, the following definitions are used when referring to GAT Clients, GAT Servers, and GAT Trusted Sources.

Table 1.1 Terminology

	Description
GAT Server	The GAT Server is the system that exposes components that can be verified by a remote GAT Client. The GAT Server may expose executables, DLLs, downloadable content (such as packages that can be downloaded by EGMs and modules that represent those installed packages), or other types of content (such as SWFs).
GAT Client	The GAT Client represents the system that wishes to challenge the GAT Server to perform verifications upon exposed components.
GAT Trusted Source	The GAT Trusted Source represents an optional system that exposes expected GAT results for verifiable components. If the GAT Client does not know whether it can trust the results from the GAT Server, it can query the GAT Trusted Source for the expected GAT results and then use that information to verify that the GAT results from the GAT Server are correct.

These relationships are illustrated in the following diagram:

Figure 1.1 Network GAT Interface Overview



1.1.2 HTTP Verb Conventions

The following table lists the standard conventions followed in this document. These conventions may not apply to every scenario. Please consult the individual resources in the following sections for the specific rules that apply.

Table 1.2 HTTP Verbs

Resource	POST create	GET read	PUT update	DELETE delete
/anyResource	Create a new item in the resource	Search the resource	Update multiple items	Delete multiple items
/anyResource/[ItemID]	Return Error - ItemID may only be assigned by the server	If exists, return ItemID; else, return Error	If exists, update ItemID; else, return Error	If exists, delete ItemID; else, return Error

Chapter 2

GAT Server Supported

HTTP Verbs

2.1 Introduction

The following table lists the resources that **MUST** be exposed by a GAT Server, along with additional features and actions that can be performed on those resources. For additional information, please refer to the sections describing each individual resource that follow.

Table 2.1 HTTP Verbs

HTTP Verbs						
Resource	POST (create)	GET (read)	PUT (update)	DELETE (delete)	Additional Features	Actions
/gat/[ver]/components	No	Yes	No	No	Search	
/gat/[ver]/components/[ID]	No	Yes	No	No		
/gat/[ver]/verificationTasks	Yes	Yes	No	No	Search	Verify
/gat/[ver]/verificationTasks/[ID]	No	Yes	No	No		

The [ver] segment of the resource **MUST** be replaced with the version number of the Network GAT Interface. A dot-delimited format **MUST** be used for the version number. For example, version "1.0" must be represented as the character string "1.0". Superfluous leading and trailing characters **MUST** be removed. For example, version "v1.0" must be represented as "1.0". For version "1.0", the appropriate resources are:

Table 2.2 Version 1.0 Resources

Version "1.0" Resource
/gat/1.0/components
/gat/1.0/components/[ID]
/gat/1.0/verificationTasks
/gat/1.0/verificationTasks/[ID]

2.2 Component Resources

A component is a software module, such as a server-side executable, DLL, image, or downloadable content, such as a game image, SWF, etc. The GAT Server **MUST** expose components that are subject to regulatory approval. Resources within this section are used to report individual components, or lists of components, that can be remotely authenticated by the GAT Client based upon specific search criteria.

2.2.1 Component Details

This resource returns information about a single component. The component is specified in the [ID] segment of the resource.

2.2.1.1 Resource Information

Table 2.3 Resource Information

HTTP Method	GET
URI	/gat/[ver]/components/[ID], where [ID] is the identifier of the component
Request Headers	Accept: application/json
Response Content Type	application/json
Response Content	component Object. See Section 2.2.1.4, Request Errors below for more detail about error scenarios.

2.2.1.2 Request Parameters:

There are no additional request parameters.

2.2.1.3 Response:

Table 2.4 component Object

Field	Type	Optional or Required	Description
componentID	String	Required	The component identifier of the resource.
componentType	String	Optional	String enumeration that identifies the type of component. See Table 4.1 for more information.
description	String	Optional	Contains an optional description of the component.
size	Number	Optional	The number of bytes for this component. Specifying this allows the client to generate its own offsets when requesting verification. This field MUST be sent if the component supports an algorithm which supports offsets.
algorithms	Array of algorithm objects	Required	At least one algorithm MUST be supported.

Table 2.5 algorithm Object

Field	Type	Optional or Required	Description
algorithmType	String	Required	Uniquely identifies the verification algorithm. See Table 4.2 for more information.
supportsSeed	Boolean	Required	Indicates whether the verification algorithm supports a seed (typically used by checksums).
supportsSalt	Boolean	Required	Indicates whether the verification algorithm supports a salt (arbitrary bytes added to the component).
supportsOffset	Boolean	Required	Indicates whether the verification algorithm supports offsetting.

2.2.1.4 Request Errors

Table 2.6 Request Errors

HTTP Error Code	Description
HTTP 404	Resource not found

2.2.2 Component Search

This resource returns an array of components based on search parameters presented by the GAT Client.

2.2.2.1 Resource Information

Table 2.7 Resource Information

HTTP Method	GET
URI	/gat/[ver]/components
Request Headers	Accept: application/json
Response Content Type	application/json
Response Content	components Object. See Section 2.2.2.4, Request Errors below for more detail about error scenarios.

2.2.2.2 Request Parameters

Table 2.8 Request Parameters

Parameter Name	Type	Optional or Required	Description
includeSoftware	Boolean	Optional	Set to true if software components SHOULD be included in the response. Set to false if software components SHOULD NOT be included in the response. If this parameter is not included in the request, a value of true MUST be assumed.
includeOS	Boolean	Optional	Set to true if OS components SHOULD be included in the response. Set to false if OS components SHOULD NOT be included in the response. If this parameter is not included in the request, a value of true MUST be assumed.
includeContent	Boolean	Optional	Set to true if content, such as content for game themes, SHOULD be included in the response. Set to false if content components SHOULD NOT be included in the response. If this parameter is not included in the request, a value of true MUST be assumed.

2.2.2.3 Response

Table 2.9 components Object

Field	Type	Optional or Required	Description
components	Array of component objects	Required	At least one component

2.2.2.4 Request Errors

Table 2.10 Request errors

HTTP Error Code	Description
HTTP 404	No resources found

2.3 Verification Task Resources

Resources within this section allow component verification tasks to be created on the GAT Server and provide access to the status of those verification tasks. Verification tasks can have various states, such as pending, in process, or complete. After verification tasks are complete, the final value of the verification request, called the verification result, will be reported.

2.3.1 Create Verification Task

This action creates a component verification task for the specified component.

2.3.1.1 Resource Information

Table 2.11 Resource Information

HTTP Method	POST
URI	/gat/[ver]/verificationTasks
Request Headers	Accept: application/json
Response Content Type	application/json
Response Content	HTTP 201 response with the HTTP Location Header set to the location of the newly created verification task. See Section 2.3.1.4, Request Errors below for more detail about error scenarios.

2.3.1.2 Request Parameters

Table 2.12 Request Parameters

Parameter Name	Type	Optional or Required	Description
componentID	String	Required	The componentID of the component on which this verification task is operating.
algorithmType	String	Required	Which authentication algorithm to run on the component.
seed	Number	Optional	The seed for the algorithm. Certain algorithms, such as checksums (CRC), use a seed to define the starting value.
salt	String	Optional	Arbitrary bytes that are prefixed to the component's byte buffer before the hash is generated (and after the offsets are applied)
startOffset	Number	Optional	The starting offset for the verification component
endOffset	Number	Optional	The ending offset for the verification component; if set to -1 (negative one), indicates that no offset is specified, which is equivalent to specifying the index of the final valid byte of the buffer

2.3.1.3 Response

Table 2.13 Response

HTTP Response Code	Description
HTTP 201 "Created"	The HTTP Location Header is set to the location of the newly created verification task.

2.3.1.4 Request Errors

Table 2.14 Request Errors

HTTP Error Code	Description
HTTP 400 "Bad Request"	The <code>seed</code> , <code>salt</code> , <code>startOffset</code> , or <code>endOffset</code> is invalid for the component and/or algorithm.
HTTP 404 "Not Found"	The resource the client attempted to perform a verification on does not exist.
HTTP 405 "Method Not Allowed"	The algorithm type requested is not supported for the component.
HTTP 413 "Request Entity Too Large"	The <code>salt</code> requested is too large for the web server to process.

2.3.2 Verification Task Details

This resource returns the status and the final result of a verification task. Verification tasks have various states, such as pending, in process, or complete. The verification task is specified in the [ID] segment of the resource. The identifier for the verification task is assigned by the GAT Server when the verification task is created.

The result of the verification is contained in the `verifyResult` field, which is represented as a string. Thus, unless the verification algorithm explicitly specifies another format, the result MUST be converted from its native binary format into a hexadecimal character representation. Each 8-bit byte MUST be converted into two hexadecimal characters in big-endian order using the ASCII characters 0-9 and A-F. The resulting string MUST be included in the `verifyResult` field included in the Verification Task resource response.

The server is allowed to remove verification task resources over time to free up resources (database, or otherwise). The schedule for removing verification tasks is up to the server to determine. However, failed and completed verification task resources SHOULD be removed every 48 hours.

2.3.2.1 Resource Information

Table 2.15 Resource Information

HTTP Method	GET
URI	/gat/[ver]/verificationTasks/[ID], where [ID] is the identifier of the verification task
Request Headers	Accept: application/json
Response Content Type	application/json

Table 2.15 Resource Information

Response Content	verificationTask Object. See Section 2.3.2.4, Request Errors below for more detail about error scenarios.
------------------	---

2.3.2.2 Request Parameters:

There are no additional request parameters.

2.3.2.3 Response Information:

Table 2.16 verificationTask Object

Field	Type	Optional or Required	Description
verificationID	Number	Required	The verification ID of this verification task.
componentID	String	Required	The componentID of the component on which this verification task is operating
verifyState	String	Required	The current state of the verification task. Allowed response values are NGI_queued, NGI_inProcess, NGI_complete and NGI_error.
algorithmType	String	Required	Which authentication algorithm to run on the component
seed	Number	Optional	The seed for the algorithm. Certain algorithms, such as checksums (CRC), use a seed to define the starting value.
salt	String	Optional	Arbitrary bytes that are prefixed to the component's byte buffer before the has is generated (and after the offsets are applied)
startOffset	Number	Optional	The starting offset for the verification component.
endOffset	Number	Optional	The ending offset for the verification component; if set to -1 (negative one), indicates that no offset is specified, which is equivalent to specifying the index of the final valid byte of the buffer
verifyResult	String	Optional	The verification result; not reported unless the verifyState is set to NGI_complete

2.3.2.4 Request Errors

Table 2.17 Request Errors

HTTP Error Code	Description
HTTP 404	Resource not found

2.3.3 Verification Task Search

This resource returns an array of verification tasks based on search parameters presented by the GAT Client.

2.3.3.1 Resource Information

Table 2.18 Resource Information

HTTP Method	GET
URI	/gat/[ver]/verificationTasks
Request Headers	Accept: application/json
Response Content Type	application/json
Response Content	verificationTasks Object

2.3.3.2 Request Parameters

Table 2.19 Request Parameters

Parameter Name	Type	Optional or Required	Description
componentID	String	Required	The componentID of the component targeted for a verification task search.

2.3.3.3 Response

Table 2.20 verificationTasks Object

Field	Type	Optional or Required	Description
verificationTasks	Array of verificationTask Objects	Required	An array of verification tasks that matched the requested component ID.

2.3.3.4 Request Errors

Table 2.21 Request Errors

HTTP Error Code	Description
HTTP 400 "Bad Request"	The component ID requested does not exist.
HTTP 404 "Not Found"	No verification tasks exist for the requested resource.

Chapter 3

GAT Trusted Source

Supported HTTP Verbs

3.1 Introduction

The following table lists the resources that MUST be exposed by a GAT Trusted Source, along with additional features and actions that can be performed on those resources. For additional information, please refer to the sections describing each individual resource that follow.

Table 3.1 HTTP Verbs

HTTP Verbs						
Resource	POST (create)	GET (read)	PUT (update)	DELETE (delete)	Additional Features	Actions
/gat/[ver]/expectedResults/[ID]	No	Yes	No	No		

The [ver] segment of the resource MUST be replaced with the version of the Network GAT Interface. A dot-delimited format MUST be used for the version. For example, version "1.0" must be represented as the character string "1.0". Superfluous leading and trailing characters MUST be removed. For example, version "v1.0" must be represented as "1.0". For version "1.0", the appropriate resources are:

Table 3.2 Version 1.0 Resources

Version "1.0" Resource
/gat/1.0/expectedResults/[ID]

3.2 Expected Results Resources

Resources within this section allow the expected results of component verification tasks to be requested from a GAT Trusted Source.

3.2.1 Expected Results Details

This resource provides expected results for the verification of a specified component.

3.2.1.1 Resource Information

Table 3.3 Resource Information

HTTP Method	GET
URI	/gat/[ver]/expectedResults/[ID], where [ID] is the identifier of the component
Request Headers	Accept: application/json
Response Content Type	application/json
Response Object	expectedResults Object. See Section 3.2.1.4, Request Errors below for more detail about error scenarios.

3.2.1.2 Request Parameters

Table 3.4 Request Parameters

Parameter Name	Type	Optional or Required	Description
algorithmType	String	Required	Algorithm type for which the expected results are required.
supportsSeed	Boolean	Required	Indicates whether a seed value should be provided for the expected result.
supportsSalt	Boolean	Required	Indicates whether a salt value should be provided for the expected result.
supportsOffsets	Boolean	Required	Indicates whether offsets should be provided for the expected result.

3.2.1.3 Response

Table 3.5 expectedResults Object

Field	Type	Optional or Required	Description
componentID	String	Required	Component Identifier; set to the componentID from the request.

Table 3.5 expectedResults Object

Field	Type	Optional or Required	Description
algorithmType	String	Required	Algorithm type; set to the algorithmType from the request.
expectedResultList	Array of expectedResult objects	Required	At least one expected result MUST be reported.

Table 3.6 expectedResult Object

Field	Type	Optional or Required	Description
seed	Number	Optional	Seed value to be used with the algorithm.
salt	String	Optional	Salt value to be used with the algorithm.
startOffset	Number	Optional	Starting offset to be used with the algorithm.
endOffset	Number	Optional	Ending offset to be used with the algorithm.
expectedResult	String	Required	Expected result from the algorithm.
resultVersion	String	Required	Identifies the specific version of the component associated with the expected result.
resultStatus	Boolean	Required	Indicates whether the expected result is approved (true) or revoked (false).
expiration	DateTime	Required	Date/time after which the expected results should no longer be used.

3.2.1.4 Request Errors

Table 3.7 Request Errors

HTTP Error Code	Description
HTTP 400 "Bad Request"	The seed, salt, startOffset, or endOffset is invalid for the component and/or algorithm.
HTTP 404 "Not Found"	Resource not found.
HTTP 405 "Method Not Allowed"	The algorithm type requested is not supported for the component.

Chapter 4

Data Types

4.1 Data Types

4.1.1 componentType Enumerations

Table 4.1 Enumerations of the componentType field

Enumeration	Description
NGI_software	A generic software component
NGI_OS	A component representing the operating system
NGI_content	A component representing content that is downloaded to a client, typically representing thin client content, such as image files, markup (HTML), or scripts.

4.1.2 algorithmType Enumerations

Table 4.2 Enumerations of the algorithmType field

Enumeration	Description
NGI_CRC16	A 16-bit cyclic redundancy check. Uses a 16-bit unsigned seed.
NGI_CRC32	A 32-bit cyclic redundancy check. Uses a 32-bit unsigned seed.
NGI_MD5	MD5 algorithm per RFC 1321. Seed is not supported, use salt.
NGI_SHA1	SHA-1 algorithm per FIPS 180-2. Seed is not supported, use salt.
NGI_SHA256	SHA-256 algorithm per FIPS 180-2. Seed is not supported, use salt.
NGI_SHA384	SHA-384 algorithm per FIPS 180-2. Seed is not supported, use salt.
NGI_SHA512	SHA-512 algorithm per FIPS 180-2. Seed is not supported, use salt.
NGI_HMACSHA1*	HMAC SHA-1 algorithm per FIPS 180-2 and FIPS 198. The HMAC key MUST be included as if it was a salt; seed and offsets are not supported.

*This algorithm is compatible with the HMAC SHA-1 algorithm required by the serial game authentication protocol GAT v3.50. It is intended that implementations using this algorithm be compatible with implementations of the HMAC SHA-1 algorithm in GAT v3.50. See GAT v3.50 for more details on the use of the HMAC SHA-1 algorithm. Note that the "(none)" convention, which is used in GAT v3.50, is not used in this specification.

Chapter 5

Sample Messages

5.1 Component Details

Request:

```
GET /gat/1.0/components/ABC_123
```

Response:

```
{
  "componentId": "ABC_123",
  "componentType": "NGI_software",
  "description": "The ABC123 Component",
  "size": 0,
  "algorithms": [
    {
      "algorithmType": "NGI_SHA1",
      "supportsSeed": false,
      "supportsSalt": true,
      "supportsOffset": false
    },
    {
      "algorithmType": "NGI_HMACSHA1",
      "supportsSeed": false,
      "supportsSalt": true,
      "supportsOffset": false
    }
  ]
}
```

5.2 Component Search

Request:

```
GET /gat/1.0/components?includeOS=false&includeContent=false
```

Response:

```
{
  "Components": [
    {
      "componentId": "ABC_123",
      "componentType": "NGI_software",
      "description": "The ABC123 Component",
      "size": 0,
      "algorithms": [
        {
          "algorithmType": "NGI_SHA1",
          "supportsSeed": false,
          "supportsSalt": true,
          "supportsOffset": false
        },
        {
          "algorithmType": "NGI_HMACSHA1",
          "supportsSeed": false,
          "supportsSalt": true,
          "supportsOffset": false
        }
      ]
    },
    {
      "componentId": "ABC_234",
      "componentType": "NGI_software",
      "description": "The ABC234 Component",
      "size": 0,
      "algorithms": [
        {
          "algorithmType": "NGI_SHA1",
          "supportsSeed": false,
          "supportsSalt": true,
          "supportsOffset": false
        },
        {
          "algorithmType": "NGI_HMACSHA1",
          "supportsSeed": false,
          "supportsSalt": true,
          "supportsOffset": false
        }
      ]
    }
  ]
}
```

5.3 Create Verification Task

Request:

```
POST
/gat/1.0/verificationTasks?componentId=ABC_123&algorithmType=NGI_SHA1
&salt=2A3B4C5D6E7F8091A708192B3C4D5E6F
```

Response:

```
/gat/1.0/verificationTasks/345678
```

5.4 Verification Task Details

Request:

```
GET /gat/1.0/verificationTasks/123456
```

Response:

```
{  
  "verificationId": 123456,  
  "componentId": "ABC_123",  
  "verifyState": "NGI_complete",  
  "algorithmType": "NGI_SHA1",  
  "salt": "1A2B3C4D5E6F708192A3B4C5D6E7F809",  
  "verifyResult": "ABC56DF718AA726FE9B72579BC45D1F2"  
}
```

5.5 Verification Task Search

Request:

```
GET /gat/1.0/verificationTasks?componentId=ABC_123
```

Response:

```
{
  "VerificationTasks": [
    {
      "verificationId": 123456,
      "componentId": "ABC_123",
      "verifyState": "NGI_complete",
      "algorithmType": "NGI_SHA1",
      "salt": "1A2B3C4D5E6F708192A3B4C5D6E7F809",
      "verifyResult": "ABC56DF718AA726FE9B72579BC45D1F2"
    },
    {
      "verificationId": 234567,
      "componentId": "ABC_123",
      "verifyState": "NGI_complete",
      "algorithmType": "NGI_SHA1",
      "salt": "2A3B4C5D6E7F8091A2B3C4D5E6F70819",
      "verifyResult": "9B72579BC45D1F2ABC56DF718AA726FE"
    }
  ]
}
```

5.6 Expected Results Detail

Request:

```
GET /gat/1.0/expectedResults?componentId=ABC_123&algorithmType=NGI_SHA1
    &supportsSalt=true
```

Response:

```
{
  "componentId": "ABC_123",
  "algorithmType": "NGI_SHA1",
  "expectedResultsList": [
    {
      "salt": "1A2B3C4D5E6F708192A3B4C5D6E7F809",
      "expectedResult": "ABC56DF718AA726FE9B72579BC45D1F2",
      "resultVersion": "1.0.0",
      "resultStatus": true,
      "expiration": "20140710T23:59:59.999-05:00"
    },
    {
      "salt": "2A3B4C5D6E7F8091A2B3C4D5E6F70819",
      "expectedResult": "9B72579BC45D1F2ABC56DF718AA726FE",
      "resultVersion": "1.0.0",
      "resultStatus": true,
      "expiration": "20140710T23:59:59.999-05:00"
    },
    {
      "salt": "2A3B4C5D6E7F8091A708192B3C4D5E6F",
      "expectedResult": "FE9B72579BC45D1F2ABC56DF718AA726",
      "resultVersion": "1.0.0",
      "resultStatus": true,
      "expiration": "20140710T23:59:59.999-05:00"
    }
  ]
}
```


END OF DOCUMENT

Released: 2016/03/14

